#### The Bugs Framework (BF) - Introduction

BF - software Developers' and Testers' "Best Friend."

#### Irena Bojanova

National Institute of Standards and Technology (NIST)



https://samate.nist.gov/BF/

#### **Know Your Weaknesses**

- They Know Your Weaknesses Do You?
- Knowing what makes your software systems vulnerable to attacks is critical,
  - → as software vulnerabilities hurt: security reliability, and availability of the system as a whole.
- Software should be free of known weaknesses

### Objective and Need

 Objective: Develop a complete, orthogonal, attributes based classification of software bugs that would improve dramatically on the current CWE definitions (vocabulary) used for defining software weaknesses, and how vulnerability classes are described for modern software development.

#### Need:

- ✓ CWE is a repository of known (reported) weaknesses in the form of a nomenclature (numbered items) that has overlaps and gaps in coverage.
- ✓ Current CWEs definitions are often inaccurate, imprecise or ambiguous, which makes it difficult to measure, express, and explain the applicability of different software quality assurance techniques or approaches for software security.
- ✓ Other existing classifications and guides also have their own problems related to coverage, accuracy and precision.
- Gap: Software security issues are often described incorrectly, and defined inaccurately,
  - → which tremendously impacts on how threats, attacks, patches, and exposures are communicated.

#### Outline

- 1. Bugs Terminology
- 2. The Bugs Framework (BF)
- 3. Existing Repositories of Bugs, Vulnerabilities, and Attacks
- 4. Problems with Current Bug Descriptions
- 5. Need for Structured, Precise, Orthogonal Approach

### **Bugs Terminology**

#### **Bugs Terminology**

- Software Weakness (Bug)
  - "A piece of code that may lead to a vulnerability." [1]
- Security Vulnerability
  - "A property of system requirements, design, implementation, or operation that could be accidentally triggered or intentionally exploited and result in a security failure." [1]
- Software Attack

"The use of an exploit(s) by an adversary to take advantage of a weakness(s) with the intent of achieving a negative technical impact(s)." [2]

[1] Black, P., Kass, M., Koo. M., Fong, E. Source Code Security Analysis Tool Functional Specification Version 1.1, NIST Special Publication 500-268 v1.1.

[2] The MITRE Corporation. Common Attack Pattern Enumeration and Classification (CAPEC), Glosary, Attack.

### **Bugs Terminology (Cont.)**

#### Security Failure

"Any event that is a violation of a particular system's explicit or implicit security policy." [1]

- √ "the source of any failure is a latent vulnerability." [1]
- ✓ "if there is a failure, there must have been a vulnerability." [1]
- Source Code

"A series of statements written in a human-readable computer programming language." [1]

A vulnerability is the result [of the exploitation] of one or more weaknesses in requirements, design, implementation, or operation. Sometimes a weakness can never result in a failure, in which case it is not exploitable and not a vulnerability. Such a weakness might be masked by another part of the software or might only cause a failure in combination with another weakness. Thus we use the term "weakness" instead of "flaw" or "defect." [1]

#### References

[1] Black, P., Kass, M., Koo. M., Fong, E. Source Code Security Analysis Tool Functional Specification Version 1.1, NIST Special Publication 500-268 v1.1.

### The Bugs Framework (BF)

### The Bugs Framework (BF)

## The Bugs Framework (BF) is a precise descriptive language for bugs.

→ allows to more accurately and precisely define software bugs or vulnerabilities.

← Factoring and restructuring of information in CWEs, SFPs, and STs, and classifications from NSA CAS, IDA SOAR, SEI-CERT, and more.

(Just as the structure of the periodic table reflects the underlying atomic structure, we are developing a taxonomy dictated by the "natural" organization of software bugs, while using as stepping stones known bugs enumerations, compendia and collections.)

#### **BF Taxonomy**


#### BF is a set of bug classes. Each BF class:

- Has an accurate and precise definition and
- Comprises:
  - ✓ Level (high or low) identifies the fault as language-related or semantic.
  - Attributes identify the software fault.
  - ✓ Causes bring about the fault.
  - ✓ Consequences to which the fault could lead.
  - ✓ Sites locations in code where the fault might occur.
- At least one attribute (underlined) identifies the software fault.
- Causes and consequences are directed graphs.
- Sites are identifiable mainly for low level classes
- BF uses precise definitions and terminology.

- BF is descriptive, not prescriptive.
  - ✓ It explains what happens.
  - ✓ There's not enough detail to usefully predict the result.
- BF is language independent.

### BF Class Graph

ClassName (ABR): <<concise definition>>.



#### **Quick Examples of BF Classes:**

- Buffer Overflow (BOF)
- Information Exposure (IEX)

Buffer Overflow (BOF)

### BF: Buffer Overflow (BOF)

#### Our Definition:

The software accesses through an array a memory location that is outside the boundaries of that array.

This definition is clearer than CWE-119: Improper Restriction of Operations within the Bounds of a Memory Buffer: "The software performs operations on a memory buffer, but it can read from or write to a memory location that is outside of the intended boundary of the buffer."

- ✓ clarifies that access is through the same buffer to which the intended boundary pertains.
- ✓ accurately, precisely, and concisely describes violation of memory safety.


#### Related CWEs, SFP and ST

CWEs are 119, 120, 121, 122, 123, 124, 125, 126, 127, 786, 787, 788, 805, 806, 823.

SFP cluster is SFP8 Faulty Buffer Access under Primary Cluster: Memory Access.

ST is the **Buffer Overflow Semantic Template**.

### BOF: Causes, Attributes, and Consequences



### BOF: Example - CVE-2014-0160 (Heartbleed)

CVE-2014-0160 (Heartbleed) description using BOF taxonomy:

Cause: Input Not Checked Properly leads to Data Exceeds Array (specifically, Too Much Data)

**Attributes:** 

Access: Read

Boundary: Above Location: Heap Data Size: Huge

**Excursion: Continuous** 

**Consequence:** IEX (if not had been cleared - CWE-226)

See: https://samate.nist.gov/BF/Examples/BOF.html

### BF Descriptions of BOF Related CWEs

CWE		BF Class							
ID	Name	BOF Cause(s)	BOF Attributes						BOF
			Access	Boundary	Location	Magnitude	Data Size	Excursion	Consequences
<u>119</u>	Improper Restriction of Operations within the Bounds of a Memory Buffer	Wrong Index/ Pointer Out of Range	any	any	any	any	any	any	any
<u>120</u>	Buffer Copy without Checking Size of Input ('Classic Buffer Overflow')	Array Too Small	<u>Write</u>	Above	any	any	any	Continuous	any
121	Stack-based Buffer Overflow	any <u>BOF</u> cause	<u>Write</u>	any	Stack	any	any	any	any
<u>122</u>	Heap-based Buffer Overflow	any <u>BOF</u> cause	<u>Write</u>	any	Неар	any	any	any	any
<u>123</u>	Write-what-where Condition	any <u>BOF</u> cause	<u>Write</u>	any	any	any	any	Discrete	any
124	Buffer Underwrite ('Buffer Underflow')	Wrong Index/ Pointer Out of Range	<u>Write</u>	Below	any	any	any	any	any
<u>125</u>	Out-of-bounds Read	PAR leads to Pointer Out of Range	Read	any	any	any	any	any	<u>IEX</u>
<u>126</u>	Buffer Over-read	any <u>BOF</u> cause	Read	Above	any	any	any	any	<u>IEX</u>
<u>127</u>	Buffer Under-read	Wrong Index/ Pointer Out of Range	Read	Below	any	any	any	any	<u>IEX</u>
<u>786</u>	Access of Memory Location Before Start of Buffer	Wrong Index/ Pointer Out of Range	any	Below	any	any	any	any	any
<u>787</u>	Out-of-bounds Write	any <u>BOF</u> cause	<u>Write</u>	any	any	any	any	any	any
788	Access of Memory Location After End of Buffer	Wrong Index/ Pointer Out of Range	any	Above	any	any	any	any	any
<u>805</u>	Buffer Access with Incorrect Length Value	Data Exceeds Array	any	Above	any	any	any	Continuous	any
806	Buffer Access Using Size of Source Buffer	Too Much Data (source size used)	any	any	any	any	any	Continuous	any
823	Use of Out-of-range Pointer Offset	Incorrect Calculation leads to PAR leads to Pointer Out of Range	any	any	any	any	any	Discrete	any

#### BOF – # of Possible Weaknesses


- Direct Causes: (2).
- Attributes: (2,2,2,3,3,2).
- Direct Consequences: (6)
- Using only the attributes Access, Boundary, Location: 8 (=2x2x2)
- Using all the attributes: 144 (=2x2x2x3x3x2)
   Using all the attributes, the 3 direct causes, and 6 consequences, without constraints:
   Total 2592 (= 3x(2x2x2x3x3x2)x6)
- Using all the attributes, the 3 direct causes (Array Too Small, Too Much Data, and Wrong Index / Pointer Out of Range), and the 6 direct consequences, with constraints: assuming that if the Cause is Array Too Small or Too Much Data then Boundary=Above and Excursion=Continuous.
   Total 1296 (=864+432).

#### Details:

- 864 (=6x144) (the cases in which cause = Wrong Index / Pointer Out of Range).
- 432 (= $2 \times (2 \times 1 \times 2 \times 3 \times 3 \times 1) \times 6$ ) (the cases in which cause = Array Too Small or Too Much Data).

Information Exposure (IEX)

### **BF: Information Exposure Model**



### BF: Information Exposure (IEX)

#### Our Definition:

Information is leaked through legitimate or side channels.

Note that leakage to an entity that should not have information is included, not just leakage that is a security concern.

IEX is related to: BOF, INJ, CIF, ENC, VRF, KMN, TRN, PRN.


#### Related CWEs and SFPs:

• CWEs related to IEX are: 8, 11, 13, 200, 201, 202, 203, 204, 205, 206, 207, 208, 209, 210, 211, 212, 213, 214, 215, 226, 244, 260, 359, 377, 385, 402, 403, 433, 488, 492, 495, 497, 498, 499, 524, 514, 515, 525, 527, 528, 529, 530, 532, 535, 536, 537, 538, 539, 540, 541,546, 548, 550, 552, 555, 598, 612, 615, 642, 651, 668.

There are many related CWEs, because information exposure can be the consequence of many weaknesses.

The only related SFP cluster is SFP Primary Cluster: Information Leak.

### IEX: Causes, Attributes, and Consequences



### IEX: Example - CVE-2017-5754 (Meltdown)

#### CVE-2017-5754 description using IEX taxonomy:

**Cause**: Hardware Behavior (CPU out-of-order execution)

**Attributes**:

<u>Data Type</u>: Any (passwords in password manager or browser, photos, emails, even business-critical

documents)

Data Sensitivity: High

Data State: Stored (in kernel-memory registries of other processes or virtual machines in the cloud)

Data Size: Huge

**Exposure: Selective** 

Frequency: On-Demand

**Channel**: Covert (cache-based timing)

Use: Any

**Consequences**: Any IEX consequence.

See: <a href="https://samate.nist.gov/BF/Examples/IEX.html">https://samate.nist.gov/BF/Examples/IEX.html</a>

#### BF Methodology

(Guidelines for developing and evaluation of BF classes)

**BF** – complete orthogonal classification of software bugs.

#### **BF Class Definition:**


- · Concise, unambiguous description of the fault(s).
- Format: "the software does <<this and that wrong>>".

#### **BF Class Taxonomy:**

- Causes
  - ✓ What leads to the fault?
- Consequences (descriptive, not prescriptive)
  - ✓ What the fault leads to?
- Attributes
  - ✓ Focus on the failure attributes of this class.
  - ✓ What parts of the system are involved in the fault?
  - ✓ What are the details of the fault?
    - What assumptions are violated? What parts of the definition are affected?
    - What doesn't happen that is supposed to? What happens that is not supposed to? What exactly goes faulty (what data or resource)? How does it happen?

#### BF Description of a Vulnerability:

- Format: <<cause>> [(specifically <<sub-cause>>)] {leads to <<cause>> [(specifically <<sub-cause>>)]} [that] allows <<bug-description-via-attributes>>, which may be exploited for <<consequence>>{, leading to <<consequence>>}
  - [] "zero or one"; {} "zero or more"



#### Let's Step Back for a Moment

Existing Repositories of Bugs, Vulnerabilities, and Attacks

Problems?

### Repositories of Bugs, Vulnerabilities, and Attacks

- Common Weakness Enumeration (CWE)
- Software Fault Patterns (SFP)
- Semantic Templates (ST)
- NSA Center for Assured Software (CAS) Weakness Classes
- Software State-of-the-Art Resources (SOAR) Matrix
- Software Engineering Institute (SEI), Carnegie Mellon University, CERT C Coding Standard
- Common Vulnerabilities and Exposures (CVE)
- Open Web Application Security Project (OWASP): Vulnerability
- Common Attack Pattern Enumeration and Classification (CAPEC)
- → Let's take a look at them...

### Common Weakness Enumeration (CWE)

**Publicly Available: Security Taxonomies,** 

Research, and Checklists

CWE is a "dictionary" of every *class* of bug or flaw in software.

More than 600 distinct classes, e.g.,

- ✓ Buffer overflow
- ✓ Directory traversal
- ✓ OS injection
- ✓ Race condition
- ✓ Cross-site scripting
- ✓ Hard-coded password
- ✓ Insecure random numbers.

CWE is a community effort.

Available in Stanford CVE-based Security SEI - CERT CO Preliminary Previous Software Taxonomies. Gary McGraw Top Ten List of Kestrel Vulnerability CLASP Research, and Vulnerability Technology Taxonomy Checklists Examples for Research Parasoft Researchers Purdue (PLOVER) Unisys MIT Lincoln Labs Security UC Berkeley Univ. of Maryland North Carolina State University (NCSU) **GMU** National SEI CERT Vulnerability Secure Coding Database Standards (NVD) CWE Common **Vulnerabilities** SANS and Exposures **National Secure** DHS (CVE) Programming Software Skills Assurance Assessment Common Body of Knowledge DHS's 'SWA' and Object 'Build Security Management In' Web Sites **Group System** Assurance Task Open Web Force Application **DHS and NIST** Security Software Assurance NSA Center for CWE Project Web Application Metrics and Tool Assured Software (OWASP) Security Compatibility Evaluation (SAMATE) Consortium (WASC) **Test Repositories** 

**Building CWE & Consensus** 

**Preliminary** 

WatchFire

**KDM Analytics** 

Other Work

James Madison

SPI Dynamics Core Security Checkmarx

Cenzic

Fig. CWE Efforts Context and Community [http://cwe.mitre.org/about/images/lg\_consensus.jpg]

#### Use of CWE

#### CWE – for use by those who:

- Create software
- Analyze software for security flaws
- Provide tools & services for finding & defending against security flaws in software.

#### CWE Compatibility and Effectiveness Program:

1. CWE Searchable

4. CWE Documentation

2. CWE Output

- 5. CWE Coverage
- 3. Mapping Accuracy 6. CWE Test Results

#### Designations for products or services:

- ✓ CWE Compatible meet 1) to 4)
- ✓ CWE Effective meet all 1) to 6)

#### Static analysis tools:

- also encouraged to map their reports to corresponding CWEs,
- so that the results from different tools could have a standard baseline to be matched and compared.

### Software Fault Patterns (SFP)

- Software Fault Patterns (SFP) is a generalized description of an identifiable family of computations that are:
  - ✓ Described as patterns with an invariant core and variant parts
  - ✓ Aligned with injury
  - ✓ Aligned with operational views and risk through events
  - ✓ Fully identifiable in code (discernable)
  - ✓ Aligned with CWE
  - ✓ With formally defined characteristics.
- → See the clusters in Table 2 here: <u>DoD Software Fault Patterns</u> (go to p.26)

### Software Fault Patterns (SFP)

- Software Fault Patterns (SFP): Classify, Identify patterns, Test cases generator.
- SFP are a clustering of CWEs into related weakness categories.
- Each cluster is factored into formally defined attributes, with:
  - ✓ Sites ("footholds")
  - ✓ Conditions
  - Properties
  - ✓ Sources
  - ✓ Sinks, etc.

- SFP categories cover 632 CWEs,
- plus there are 8 deprecated CWEs
- → So, the CWEs defined as weaknesses total 640.

#### In addition, there are:

- 21 primary clusters
- 62 secondary clusters
- 310 discernible CWEs
- 36 unique SFPs.

### Semantic Templates (ST)

Semantic templates (ST) build mental models, which help us understand software weaknesses.

ST factor out chains of causes, resources and consequences that are present in CWEs.

Each ST is a human and machine understandable representation of the following phases:

- 1. Software faults that lead to a weakness
- 2. Resources that a weakness affects
- 3. Weakness attributes
- 4. Consequences/failures resulting from the weakness.

Fig. Phrases in descriptions and common consequences of <u>CWE-120</u>, colored according to ST: Fault, Resource/Location, <u>Weakness</u>, <u>Consequence</u>

CWE-120: Buffer Copy without Checking Size of Input ('Classic Buffer Overflow')


Description Summary: The program copies an input buffer to an output buffer without verifying that the size of the input buffer is less than the size of the output buffer, leading to a buffer overflow.

Extended Description: A buffer overflow condition exists when a program attempts to put more data in a buffer than it can hold, or when a program attempts to put data in a memory area outside of the boundaries of a buffer. The simplest type of error, and the most common cause of buffer overflows, is the "classic" case in which the program copies the buffer without restricting how much is copied.


Common Consequences: Buffer overflows often can be used to execute arbitrary code, which is usually outside the scope of a program's implicit security policy. This can often be used to subvert any other security service. Buffer overflows generally lead to crashes. Other attacks leading to lack of availability are possible, including putting the program into an infinite loop.


#### ST

ST build mental models, which help us understand software weaknesses.



#### **Buffer Overflow Semantic Template**





#### Other Repositories/Classifications

- The National Security Agency (NSA) Center for Assured Software (CAS) defines Weakness
  Classes in its "Static Analysis Tool Study Methodology".
- The Software State-of-the-Art Resources (SOAR) Matrix:
  - Defines and describes a process for selecting and using appropriate analysis tools and techniques for evaluating software for software (security) assurance.
  - In particular, it identifies types of tools and techniques available for evaluating software, as well as technical objectives those tools and techniques can meet.
- Software Engineering Institute (SEI), Carnegie Mellon University, CERT C Coding Standard
- Open Web Application Security Project (OWASP): Vulnerability
- → See <u>BF website</u>.

## Common Vulnerabilities and Exposures (CVE) Common Attack Pattern Enumeration and Classification (CAPEC)

- CVE is a list of instances of security vulnerabilities in software.
  - More than 9000 CVEs assigned in 2014 Heartbleed is CVE-2014-0160.
  - NIST National Vulnerability Database (NVD) adds fixes, severity ratings, etc. for CVEs.
- CAPEC is a dictionary and classification taxonomy of known attacks
- → See: <a href="https://cve.mitre.org/">https://cve.mitre.org/</a>

# Problems with Current Bug Descriptions

### **Problems With Current Bug Descriptions**

The rise in cyberattacks lead to considerable community and government efforts to record software weaknesses, faults, failures, vulnerabilities and attacks.

→ However, none of the resulting repositories/enumerations are complete nor close to formal.

### CWE – the Best, but also ...

- CWE is widely used:
  - ✓ By far the best dictionary of software weaknesses.
  - ✓ Many tools, projects, etc. are based on CWE.
- However, in CWE:
  - ✓ For very formal, exacting work, the Definitions are often inaccurate, imprecise or ambiguous.
  - ✓ Entrees are "coarse grained" each CWE bundles many stages, such as likely attacks, resources affected and consequences..
  - ✓ The coverage is uneven –
    some combinations of attributes well represented and others not appearing at all.

## CWE - Imprecise Definitions

CWE-78: Improper Neutralization of Special Elements used in an OS Command ('OS Command Injection'):

"The software constructs all or part of an OS command using externally-influenced input from an upstream component, but it does not neutralize or incorrectly neutralizes special elements that could modify the intended OS command when it is sent to a downstream component."

→ Note that "using input", "intended command", and "incorrectly neutralizes" are imprecise!

## CWE – Imprecise Definitions

- Looking just at the cluster of buffer overflows, we see many problems.
- Here is CWE-119, the "root" of buffer overflows.

CWE-119: Improper Restriction of Operations within the Bounds of a Memory Buffer:

"The software performs operations on a memory buffer, but it can read from or write to a memory location that is outside of the intended boundary of the buffer."

- → Note that "read from or write to a memory location" is not tied to the buffer!
- → Strictly speaking, this definition is not correct, as any variable is "a memory location that is outside of the intended boundary of the buffer."
- → Our definition says that the software can read or write through the buffer a memory location that is outside that buffer.

And, this is just one example.

## CWEs - Overlaps or Gaps in Coverage

### e.g. Buffer Overflow

Writes before start and after end:

CWE-124: Buffer Underwrite ('Buffer Underflow')

CWE-120: Buffer Copy without Checking Size of Input ('Classic Buffer Overflow')

#### versus

Writes (not expressed in title) in stack and heap:

CWE-121: Stack-based Buffer Overflow CWE-122: Heap-based Buffer Overflow.

Reads before start and after end:

CWE-127: Buffer Under-read CWE-126: Buffer Over-read

#### but

No reads from stack and heap.

... while slight variants go on and on:

- CWE-123: Write-what-where Condition
- CWE-125: Out-of-bounds Read
- CWE-787: Out-of-bounds Write
- CWE-786: Access of Memory Location Before Start of Buffer
- CWE-788: Access of Memory Location After End of Buffer
- CWE-805: Buffer Access with Incorrect Length Value
- CWE-823: Use of Out-of-range Pointer Offset

## CWEs - Overlaps or Gaps in Coverage

The empty cells in the table show the overlaps and gaps in the CWEs coverage of buffer overflow options with the following attributes considered:

- √ read/write
- √ before/after
- √ stack/heap

	Before	After	Either End	Stack	Heap
Read	CWE-127	CWE-126	CWE-125		
Write	CWE-124	CWE-120	CWE-123 CWE-787	CWE-121	CWE-122
Either R/W	CWE-786	CWE-788			

## CWE - Gaps -> Use of Approximate CWE

CVE-2018-19842 described with BF BOF

https://docs.google.com/document/d/11mbdNYAu8EH-IPsacmSYhZhOYkkiSCEDUULbYFAGkM4/edit

<u>Note</u>: This CVE was identified by Kevin Greene (MITRE) as an illustration of assigning an approximate CWE (specifically, the generic <u>CWE-125 Out-of-bounds Read</u>), because there is no exact CWE about *Read* from *Above* the boundary of a buffer on the *Stack*.

### CWEs - Too Detailed

### e.g. Path Traversal – CWE for every tiny variant:

- CWE-23: Relative Path Traversal
- CWE-24: Path Traversal: '../filedir'
- CWE-25: Path Traversal: '/../filedir'
- CWE-26: Path Traversal: '/dir/../filename'
- CWE-27: Path Traversal: 'dir/../../filename'
- CWE-28: Path Traversal: '..\filedir'
- CWE-29: Path Traversal: '\..\filename'
- CWE-30: Path Traversal: '\dir\..\filename'
- CWE-31: Path Traversal: 'dir\..\..\filename'
- CWE-32: Path Traversal: '...' (Triple Dot)
- CWE-33: Path Traversal: '....' (Multiple Dot)
- CWE-34: Path Traversal: '....//'
- CWE-35: Path Traversal: '.../...//'

Buffer overflow isn't the only cluster with problems.

Looks like, it is a waste to have CWEs for every tiny variant of path traversal.

And if some other variant were identified, a new CWE would have to be created.

## CWEs - Not Always Easy to Find

Example on how would you find this is a CWE relates to Information Exposure

CWE-433: Unparsed Raw Web Content Delivery

- SFP researchers found it by an automated process and put it in SFP Secondary Cluster: Exposed Data.
- But if a person had to do this, the name of the CWE does not help much.

# Software Fault Patterns (SFP) – Improve on CWEs

- SFP overcomes the problem of combinations of attributes in CWE.
- → For example, the SFP factored attributes are more clear than the irregular coverage of CWEs.

**CWE-119:** Improper Restriction of Operations within the Bounds of a Memory Buffer

**Summary:** The software performs operations on a memory buffer, but it can read from or write to a memory location that is outside of the intended boundary of the buffer.

**Extended description:** Certain languages allow direct addressing of memory locations and do not automatically ensure that these locations are valid for the memory buffer that is being referenced. This can cause read or write operations to be performed on memory locations that may be associated with other variables, data structures, or internal program data. As a result, an attacker may be able to execute arbitrary code, alter the intended control flow, read sensitive information, or cause the system to crash.

**CWE-120:** Buffer Copy without Checking Size of Input ('Classic Buffer Overflow')

Summary: The program copies an input buffer to an output buffer without verifying that the size of the input buffer is less than the size of the output buffer, leading to a buffer overflow. **Extended Description:** A buffer overflow condition exists when a program attempts to put more data in a buffer than it can hold, or when a program attempts to put data in a memory area outside of the boundaries of a buffer.

**Common Consequences:** Buffer overflows often can be used to execute arbitrary code. Buffer overflows generally lead to crashes.

	Parameters	Parameters Buffer location		Access kind		Access position		Boundary exceeded	
		heap	stack	write	read	inside	outside	lower	upper
	119 - Improper Restriction of Operations within Bounds of Buffer	V	V	V	V		$\sqrt{}$	V	V
	120 - Buffer Copy without Checking Size of Input	<b>√</b>	<b>√</b>	<b>√</b>		<b>V</b>		1	<b>√</b>
	121 - Stack Overflow		$\sqrt{}$	$\sqrt{}$		$\sqrt{}$		$\sqrt{}$	$\sqrt{}$
	122 - Heap Overflow	$\sqrt{}$		$\sqrt{}$		<b>V</b>		V	$\sqrt{}$
	123 - Write- what-where Condition	$\sqrt{}$	$\sqrt{}$	$\sqrt{}$				V	<b>V</b>
	124 - Buffer Underwrite	$\sqrt{}$	$\sqrt{}$	$\sqrt{}$			$\sqrt{}$	$\sqrt{}$	
	125 - Out-of- bounds read	$\sqrt{}$	$\sqrt{}$		$\sqrt{}$			V	$\sqrt{}$
	126 - Buffer Overread	$\sqrt{}$	$\sqrt{}$				$\sqrt{}$		
	127 - Buffer Underread	$\sqrt{}$	$\sqrt{}$		<b>V</b>		$\sqrt{}$	V	

# Semantic Templates (ST) – Improve on CWEs, too

- STs build mental models, which help us understand software weaknesses.
- Each ST is a human and machine understandable representation of:
  - Software faults that lead to a weakness
  - 2. Resources that a weakness affects
  - 3. Weakness attributes
  - 4. Consequences/failures resulting from the weakness.

CWE-119: Improper Restriction of Operations within the Bounds of a Memory Buffer

Summary: The software performs operations on a memory buffer, but it can read from or write to a memory location that is outside of the intended boundary of the buffer.

Extended description: Certain languages allow direct addressing of memory locations and do not automatically ensure that these locations are valid for the memory buffer that is being referenced. This can cause read or write operations to be performed on memory locations that may be associated with other variables, data structures, or internal program data. As a result, an attacker may be able to execute arbitrary code, alter the intended control flow, read sensitive information, or cause the system to crash.

CWE-120: Buffer Copy without Checking Size of Input ('Classic Buffer Overflow')


Summary: The program copies an input buffer to an output buffer without verifying that the size of the input buffer is less than the size of the output buffer, leading to a buffer overflow.

Extended Description: A buffer overflow condition exists when a program attempts to put more data in a buffer than it can hold, or when a program attempts to put data in a memory area outside of the boundaries of a buffer.

Common Consequences: Buffer overflows often can be used to execute arbitrary code. Buffer overflows generally lead to crashes.

	Parameters	Buffer location		Access kind		Access position		Boundary exceeded	
		heap	stack	write	read	inside	outside	lower	upper
	119 - Improper Restriction of Operations within Bounds of Buffer	$\checkmark$	$\sqrt{}$	$\checkmark$	<b>√</b>		$\sqrt{}$	<b>√</b>	<b>√</b>
	120 - Buffer Copy without Checking Size of Input	$\sqrt{}$	$\sqrt{}$	$\sqrt{}$		$\sqrt{}$		<b>√</b>	V
	121 - Stack Overflow		$\sqrt{}$	$\sqrt{}$		$\sqrt{}$		$\sqrt{}$	$\sqrt{}$
	122 - Heap Overflow	$\checkmark$		$\checkmark$		$\sqrt{}$		√	$\sqrt{}$
	123 - Write- what-where Condition	$\sqrt{}$	$\sqrt{}$	$\sqrt{}$				$\sqrt{}$	$\sqrt{}$
	124 - Buffer Underwrite	$\sqrt{}$	$\sqrt{}$	$\sqrt{}$			$\sqrt{}$	√	
	125 - Out-of- bounds read	$\sqrt{}$	$\sqrt{}$		$\sqrt{}$			$\sqrt{}$	$\sqrt{}$
	126 - Buffer Overread	$\sqrt{}$	$\sqrt{}$		$\sqrt{}$		$\sqrt{}$		$\sqrt{}$
	127 - Buffer Underread	$\sqrt{}$	$\sqrt{}$		$\sqrt{}$		$\sqrt{}$	$\sqrt{}$	

# Semantic Templates (STs) – Improve on CWEs, too



	Parameters		ffer ation	Access kind Acces		Access	position	Boundary exceeded	
		heap	stack	write	read	inside	outside	lower	upper
	119 - Improper Restriction of Operations within Bounds of Buffer	$\checkmark$	$\sqrt{}$	V	V		V	$\sqrt{}$	V
	120 - Buffer Copy without Checking Size of Input	$\sqrt{}$	$\sqrt{}$	$\sqrt{}$		$\sqrt{}$		<b>V</b>	$\sqrt{}$
	121 - Stack Overflow		$\sqrt{}$	$\sqrt{}$		$\sqrt{}$		$\sqrt{}$	$\sqrt{}$
	122 - Heap Overflow	$\sqrt{}$		$\checkmark$		$\sqrt{}$		$\sqrt{}$	$\sqrt{}$
	123 - Write- what-where Condition	$\sqrt{}$	$\sqrt{}$	$\sqrt{}$				$\sqrt{}$	$\sqrt{}$
	124 - Buffer Underwrite	$\sqrt{}$	$\sqrt{}$	$\sqrt{}$			$\sqrt{}$	$\sqrt{}$	
	125 - Out-of- bounds read	$\sqrt{}$	$\sqrt{}$		$\sqrt{}$			$\sqrt{}$	$\sqrt{}$
	126 - Buffer Overread	$\sqrt{}$	$\sqrt{}$		$\sqrt{}$		$\sqrt{}$		$\sqrt{}$
	127 - Buffer Underread	$\sqrt{}$	$\sqrt{}$		$\sqrt{}$		$\sqrt{}$	$\sqrt{}$	

### **But SFP & ST Also Have Problems**

- Software Fault Patterns (SFP):
  - ✓ are an excellent advance
  - ✓ "factor" weaknesses into parameters,
  - ✓ But:
    - do not include upstream causes or consequences, and
    - are based solely on CWEs.
- → SFPs do not tie fault clusters to:
  - causes or chains of fault patterns
  - consequences of a particular vulnerability.
- → Since SFP were derived from CWEs, more work is needed for embedded or mobile concerns, such as, battery drain, physical sensors (e.g. Global Positioning System (GPS) location, gyroscope, microphone, camera) and wireless communications.

Note: SFP is coupled with a meta-language, Semantics of Business Vocabularies and Rules (SBVR), in which causes, threats, consequences, etc. may be expressed. However, SFP does not have an integrated means of expressing them.

### **But SFP & ST Also Have Problems**

- Semantic Templates (ST):
  - ✓ Collect CWEs into four general areas:
    - Software-fault
    - Weakness
    - Resource/Location
    - Consequences.
  - ✓ But:
    - are guides to aid human comprehension.
- \_\_\_\_\_\_
- The other existing bug descriptions also have their own limitations.
- They are based on CWEs and don't go beyond CWEs.

# → Need for Structured, Precise, Orthogonal Approach

# Need for Structured, Precise, Orthogonal Approach


- ➤ Without accurate and precise classification and comprehension of all possible types of software bugs, the development of reliable software will remain extremely challenging.
- As a result the newly delivered and the legacy systems will continue having security holes despite all the patching to correct errant behavior.


We don't (yet) know the best structure for bugs descriptions.


But, for analogies on what we are embarking on, let's look at some well-know organizational structures in science ...

### Periodic Table & Others to Describe Molecules

- Greeks used the terms element and atom.
   Aristotle: substances are a mix of Earth, Fire, Air, or Water.
- Alchemists cataloged substances, such as alcohol, sulfur, mercury, and salt. (note: Lavoisier had light and caloric on his 33 elements list!)
- Periodic table reflects atomic structure & forecasts properties of missing elements.








(±) 1, 2, 3, 9-tetrahydro-9-methyl-3-[(2-methyl-1Himidazol-1-yl)methyl]-4H-carbazol-4-one

Zofran ODT has a chemical formula ( $C_{18}H_{19}N_3O$ ), structural formula (picture), and a detailed name.

### Tree of Life


Discoveries of more than 1,000 new types of Bacteria and Archaea over the past 15 years have dramatically rejiggered the Tree of Life to account for these microscopic life forms.

- Divides life into three domains:
  - ✓ Bacteria
  - ✓ Archaea
  - ✓ Eukaryotes.
- Clearly shows "life we see around us plants, animals, humans" and other Eukaryotes – represent a tiny percentage of world's biodiversity.




## Geographic Coordinate System

Specify Any Terrestrial Location using Latitude, Longitude, and Elevation.



#### **Elevation Histogram of the Earth's Crust**



Geographic Coordinate System (Source: Wikipedia)

## Precise Medical Language

Medical professionals have terms to precisely name muscles, bones, organs, conditions, diseases, etc.





Figure 2: Computed tomography of a comatose patient with a left temporal epidural haematoma, right parenchymal temporal lobe haematoma, and a right convexity subdural haematoma before and after craniotomy and evacuation of haematomas

- The caption uses precise medical terminology.
- They are not trying to obfuscate.
- They are "painting a picture" (adding arrows and circles) with words.

→ So, just as a doctor would be hampered by only being able to say, "this thingy here", software assurance work is more difficult, because of the lack of a precise common vocabulary (ontology).

## Questions → Next



Irena.Bojanova@nist.gov https://samate.nist.gov/BF/

Details on the developed so far BF classes → in the next presentation in a moment.